


Kombimaskine med 5 funktioner C400

- ☐ Rundsav
- ☐ Vertikalfræser
- ☐ Høvl
- ☐ Tykkelseshøvl
- ☐ Langhulsborer

5 works combines machine C400

- ☐ Circular saw
- ☐ Shaper
- ☐ Surface planer
- ☐ Thickness machine
- ☐ Spindle moulder mortiser



**SICAR**Optional accessories
Valgfrit tilbehør

Planer	Høvl	Unit	C400
Working table	Arbejdsbord	mm	400x1800
Cutter block diameter	Skæreflade diameter	mm	70
Cutterblock rotation speed	Skæreflade rotationshastighed	r.p.in	s700
Knives Dimensions(3 knives)	Dimensioner høvljern(3 knive)	mm	400x25x3
Max table adjustment	Max bordjustering	mm	4

Thickneser	Tykkelseshøvl	Unit	C400
Working table	Arbejdsbord	mm	400x760
Feeding speed	Tilførselshastighed	in/1'	7
Working height	Arbejdshøjde	mm	4-220

Mortiser	Langhulsboring	Unit	C400
Working table	Arbejdsbord	mm	250x500
Longitudinal/Trasversal/ Vertical stroke	Langsgående /tværgående/ Vertikal	mm	205/95/90
Chuck (M18*1.5-S)	Spindel(M18*1.5-S)	mm	0-16

Circular saw	Rundsav	Unit	C400
Working table	Arbejdsbord	mm	326x111 2
Shaft rotation/Engraver speed	Omdrejningshastighed	r.p.m.	4500/7000
Blade diameter	Klangediameter	mm	300x30
Cutting height at 45°/90°	Skærehøjde ved 45°/90°	mm	75/100
Max cutting width between blade and fence	Max skærebredde mellem klinge og anslag	mm	730
Engraver blade diameter	Klangediameter	mm	90x22

Shaper	Vertikalfræser	Unit	C400
Working tables	Arbejdsbord	mm	326x1112
Shaft rotation speeds	Rotationshastighed	r.p.m.	2000/3100 4400/7000
Standard shaft diameter	Standard skaftdiameter	mm	30/35/50
Shaft vertical stroke	Vertikal vandring	mm	115
Max. tool diameter	Max. værktøjsstørrelse	mm	180
Max. tenoning depth	Max dybde	mm	65

Standard accessories	Standard tilbehør	Unit	C400
3 - phase motor power	3 - faset motorydelse	H P - KW	4,0 -3,0
Dimension Carriage	Transportslæde	mm	1800x315
Weight	Vægt	kg	680

Optional accessories	Valgfrit tilbehør	Unit	C400
Single- phase motor	Enkeltfaset motor	HP - KW	4,0 - 3,0
Increased 3 - phase motor	3-faset forøget motor	HP - KW	5,5 - 4,0
Spiral cutter heads	Spiralfræsere		•
Moving wheels	Transporthjul		•
Contouring fence	Tappeboks		•
Wescott (Diameter)	Wescott (Diameter)	mm	Ø 0- 16
Dimension Carriage	Transportslæde	mm	2200/2600
Spindle moulder extension output table	Forlængerbord til fræser	mm	288,250
Tenoning protection with shelf	Beskyttelse til tappeboks med hyld	mm	326X500

Spiral Cutter Heads
Spiralfræser


Moving wheels



Transporthjul

Wescott (Chuck)
Wescott (Borepatron)Mortiser Bits N°6
Langhulsbor -6

Tenoning

Contouring fence
TappeboksCutter Heads N°7
Skærehoveder N°7Angle Ruler Pro
Vinkelanslag ProPlaner Knives
HøvljernSaw Blade
savklinge

Engraver

