Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

k

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Basta Vinyl Cleaner

· Article number: 4909614

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Process category

PROC7 Industrial spraying PROC11 Non industrial spraying

· Application of the substance / the mixture Surface cleaning

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Basta Active Car Care A/S

2820 Gentofte

Denmark Tel: +45 45 881 882

Fax: +45 45 873 874

E-mail: info@bastacarcare.dk

· Further information obtainable from: info@bastacarcare.dk

• 1.4 Emergency telephone number: During normal opening hours: Tel: +45 45 881 882

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Active substance with propellant

· Dangerous components:		
CAS: 106-97-8	butane (containing < 0.1% butadiene (203-450-8))	
EINECS: 203-448-7	S: 203-448-7 Flam. Gas 1, H220; Press. Gas (Comp.), H280	
CAS: 109-59-1	2-isopropoxyethanol	2.5-<10%
EINECS: 203-685-6	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 7320-34-5	tetrapotassium pyrophosphate	1.0-<2.5%
EINECS: 230-785-7 Eye Irrit. 2, H319		
	Mixture Alkylglucocide / C10 Alcoholethoxylaat	1.0-<2.5%
	Eye Dam. 1, H318; Acute Tox. 4, H312	
CAS: 74-98-6	propane	1.0-<2.5%
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas (Comp.), H280	
CAS: 67-63-0	propan-2-ol	1.0-<2.5%
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 1336-21-6	ammonia	≤0.1%
EINECS: 215-647-6	Skin Corr. 1B, H314; Aquatic Acute 1, H400; Acute Tox. 4, H302	
1		

• Ingredients according to detergents guidline 648/2004/EC aliphatic hydrocarbons ≥15 - <30%</td> phosphates, non-ionic surfactants, perfumes <5%</td>

· Additional information:

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- \cdot After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- \cdot For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 $^{\circ}$ C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

(Contd. on page 4)

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

(Contd. of page 3)

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the wo	rkplace:
---	----------

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL	Short-term value: 1810 mg/m³, 750 ppm
	Long-term value: 1450 mg/m³, 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

OEL	Short-term value:	3600 mg/m^3 ,	2000 ppm
	Long-term value:	1800 mg/m^3 ,	1000 ppm

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m³, 400 ppm

· DNELs

Mixture Alkylglucocide / C10 Alcoholethoxylaat

Minute Timi guessias (510 Missilon) mut		
Oral	DNEL	35.7 mg/kg bw/day (Consumer)
Dermal	DNEL	357000 mg/kg bw/day (Consumer)
		595000 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-systemic	420 mg/m3 (Worker)
67-63-0 propan-2-ol		
Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer)
		888 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	89 mg/m3 (Consumer)
		500 mg/m3 (Worker)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Filter A/P2

\cdot Protection of hands:

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

(Contd. on page 5)

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

(Contd. of page 4)

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

• **pH-value at 20** °C: 10.3

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** -0.5 °C

· Flash point: -60 °C

· Flammability (solid, gas): Not applicable.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

 $\cdot \ Explosion \ limits:$

Lower: 1.5 Vol % **Upper:** 13.0 Vol %

· Vapour pressure at 20 °C: 2100 hPa

Density at 20 °C:
 Relative density
 0.92 g/cm³
 Not determined.

Vapour densityEvaporation rateNot determined.Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

Organic solvents: 16.0 % **Water:** 75.6 %

(Contd. on page 6)

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

(Contd. of page 5)

Solids content: 2.0 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
109-59-1 2	109-59-1 2-isopropoxyethanol	
Oral	LD50	5560 mg/kg (rat)
Dermal	LD50	1600 mg/kg (rbt)
Inhalative	LC50/4 h	1930 mg/l (mus)
Mixture A	Mixture Alkylglucocide / C10 Alcoholethoxylaat	
Oral	LC50	2000-5000 mg/kg (rat)
Dermal	LD50	2000-5000 mg/kg (rat)
Inhalative	LC50	>20 mg/L (rat)
67-63-0 pi	67-63-0 propan-2-ol	
Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50/6h	25000 mg/m3 (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicit	· Aquatic toxicity:	
7320-34-5 tetra	7320-34-5 tetrapotassium pyrophosphate	
LC50 >750 mg/l (Fish (Golden Orfe))		
	>750 mg/l (Fish (leuciscus idus, 48hr))	
Mixture Alkylş	glucocide / C10 Alcoholethoxylaat	
EC50 (72h)	>10-100 mg/l (algae)	
LC50/96h	>10-100 mg/l (Oncorhynchus mykiss (96h))	
EC50/48h	>10-100 mg/l (Daphnia Magna 48h)	
EC50	>10-100 mg/l (Daphnia Magna 48h)	
67-63-0 propar	67-63-0 propan-2-ol	
LOEC (8 days)	1000 mg/l (algae)	
LC50/96h	9640 mg/l (Pimephales promelas)	
LC50 (24h)	9714 mg/l (Daphnia magna)	

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion
--------------------------------------	------

<u> </u>	
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	UN1950
· 14.2 UN proper shipping name· ADR, ADN· IMDG· IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable

(Contd. on page 8)

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases.
Class Label	2 3F Gases. 2.1
	2.1
ADN ADN/R Class:	2 5F
	2. 31
IMDG, IATA	
2	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	- Guses.
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre: Segregation as for class 9. Stow "separated from"
	class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate
	subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
14.7 Transport in bulk according to A	nnex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
ADR Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
• •	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	_
Limited quantities (LQ)	1L C-dF0
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	Not permitted as Excepted Quantity

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

(Contd. of page 8)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

Class	Share in %
Wasser	75-<100
NK	10-<25

- · VOC-CH 15.98 %
- · VOC-EU 146.5 g/l
- · Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

- · Department issuing SDS: Research & Development
- · Contact: info@bastacarcare.dk
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

(Contd. on page 10

(Contd. of page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 23.05.2017 Version: 4 Revision: 22.05.2017

Trade name: Basta Vinyl Cleaner

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1